

Reverberant Room Sound Pressure Level from Sound Power Point Source

By Tom Irvine

September 15, 2022

Statistical Energy Analysis approach.

Assume a point source radiating uniformly into a diffuse, reverberant field.

$\langle E \rangle$	Acoustical energy
V	Volume
$\langle p^2 \rangle$	Spatial average of the mean square pressure
ρ	Gas density
c	Gas speed of sound
Π_{in}	Input power
η	Loss factor
ω	Angular frequency
f	Frequency
T_R	Reverberation Time (60 dB decrease)

The energy equation is taken from Reference 1, equation (5.35).

$$\langle E \rangle = \frac{V}{\rho c^2} \langle p^2 \rangle \quad (1)$$

$$\langle p^2 \rangle = \frac{\rho c^2}{V} \langle E \rangle \quad (2)$$

The power is calculated from energy per Reference 1, equation (5.36) with the interior surface absorption coefficient set to zero for conservatism.

$$\Pi_{in} = \eta \omega \langle E \rangle \quad (3)$$

$$\langle E \rangle = \frac{1}{\eta \omega} \Pi_{in} \quad (4)$$

By substitution,

$$\langle p^2 \rangle = \frac{\rho c^2}{\eta \omega V} \Pi_{in} \quad (5)$$

$$\langle p^2 \rangle = \frac{\rho c^2}{2\pi f \eta V} \Pi_{in} \quad (6)$$

The loss factor is related to reverberation time via Reference 2.

$$\eta = \frac{2.2}{f T_R} \quad (7)$$

By substitution,

$$\langle p^2 \rangle = \frac{\rho c^2 f T_R}{(2.2) 2 \pi f V} \Pi_{in} \quad (8)$$

$$\langle p^2 \rangle = \frac{\rho c^2 T_R}{4.4 \pi V} \Pi_{in} \quad (9)$$

Orbital Reef Requirement: The system will provide a reverberation time in the habitable volume of less than 0.6 second within the 500 Hz, 1 kHz, and 2 kHz octave bands.

So assume $T_R = 0.6$ sec for all bands.

References

1. R. Lyon, Machinery Noise and Diagnostics, Butterworth-Heinemann, Boston, MA, 1987. (Section 5.8)
2. J. Wijker, Random Vibrations in Spacecraft Structure Design, Springer, New York, 2009. Equations (4.117) through (4.122) and page 272.